




Unit: mm



Pan 360°

Tilt 70°



Features

- Die-cast aluminium shell with polycarbonate bubble
- Surface mount
- Indoor/Outdoor use
- Built to IP66
- 1/3" CCD true Day/ Night colour CCD
- Removable IR cut filter
- High resolution: 520 TVL
- 0.3 Lux @ F1.2, 0.0 Lux @ F1.2 with IR Leds ON
- 18 IR LEDs
- IR Distance: 18m
- 3.3~12mm lens
- Operates on 12VDC/24VAC
- 4 privacy masking zones
- Second video output
- Service lead for easy configuration included

Technical Data

General Specifications

Camera	1/3" CCD True Day/ Night Colour CCD with removable IR Cut filter
Sensitivity	0.3Lux @ F1.2
Resolution	520TVL
Signal to Noise Ratio	50dB
On Screen Display	Yes
White Balance	Automatic, One touch or Manual
BLC	4 Levels
AGC	3 Levels
DNR	4 Levels (Digital Noise Reduction)
Onscreen Camera ID	Yes
Day/Night configuration	Yes
Sync	Internal, Line-locked
Motion Detection	4 configurable zones
Privacy Masking	4 configurable zones
Mirror	Reversal of image in horizontal plane
Sharpness	Edge enhancement
Voltage	DC 12V(10 - 20V) or AC24V(20 - 28V)
Power Consumption	DC12V : 5.7 W max., AC24V : 5.3 W max
Operation Temperature	-10°C ~ +55°C
Storage Temperature	-20°C ~ +70°C

Lens

Type	Aspherical Varifocal lens
Focal length	3.3~12mm F1.5
Iris	DC Auto Iris or Fixed

Order Codes

Vi-C14WC 75mm Infrared Vandal Mini Dome, White

Accessories

Vi-B7	Wall mount bracket, aluminium
Vi-E8	Heater kit for operation down to -40°C
Vi-PSU15	Power Supply, 12V DC 1A in-line

Overview

This true day/night vandal proof dome with integrated infrared will give you the best quality pictures no matter what the lighting conditions are. It is ideal for general outdoor use and installations in where there is high risk of abuse.

Videoswitch, Ocean House, Redfields Industrial Park, Redfields Lane, Church Crookham, Hants GU52 0RD

www.videoswitch.co.uk

Tel: 01252-851510 Fax: 01252-851296 Email: sales@videoswitch.co.uk

This product is designed and manufactured to the highest standards within our ISO9000 certified quality assurance system. It is certified to meet the CE mark requirements in accordance with the 89/336/EEC Electromagnetic Compatibility and 73/23/EEC Low Voltage directives. Due to a policy of ongoing product development, specifications may change without notice.



Vsd550i

Videoswitch, Ocean House, Redfields Industrial Park, Redfields Lane, Church Crookham, Hants GU52 0RD

www.videoswitch.co.uk

Tel: 01252-851510 Fax: 01252-851296 Email: sales@videoswitch.co.uk

This product is designed and manufactured to the highest standards within our ISO9000 certified quality assurance system. It is certified to meet the CE mark requirements in accordance with the 89/336/EEC Electromagnetic Compatibility and 73/23/EEC Low Voltage directives. Due to a policy of ongoing product development, specifications may change without notice.



Vsd550i